




City of Santa Clara
Building Division
1500 Warburton Ave.
Santa Clara, CA 95050
www.santaclaraca.gov

Building Division: (408) 615-2440
Email: Building@santaclaraca.gov
Permit Center: (408) 615-2420
Email: PermitCenter@santaclaraca.gov
Automated Inspection Scheduling System: (408) 615-2400


WALL AND CEILING COVERINGS

EXTERIOR PLASTER (STUCCO)




WEEP SCREEDS
Section 2512.1.1 and 2512.1.2
ASTM C1063-03, Section 7.11.5

INTERIOR AND EXTERIOR PLASTER (STUCCO)



INTERIOR PLASTER Section 2511




EXTERIOR PLASTER Section 2512 and ASTM C926

Application of Portland Cement based Plaster shall be ASTM C926.
Minimum 3 coats are required.


APPLICATION AND FINISHING OF GYPSUM BOARD PER 2010 CBC SECTIONS 2508, 2509, 2512 AND ASTM C840

JOINT TREATMENT



Section 2508.4, Exception 2

APPROVED BACKER BOARDS FOR STALL SHOWERS AND TUB/SHOWER ENCLOSURES




NOTES:

WATER RESISTANT GYPSUM BOARD (GREEN BOARD) IS NOT PERMITTED AS BACKING IN AREAS SUBJECT TO WATER CONTACT SUCH AS STALL SHOWERS AND TUB/SHOWER ENCLOSURES OR SUBJECT TO HIGH HUMIDITY AREAS SUCH AS SAUNAS, STEAM ROOMS OR GANG SHOWERS.

Section 2509.5

APPLICATION AND FINISHING OF GYPSUM BOARD PER 2010 CBC SECTIONS 2508, 2509, 2512 AND ASTM C840




Fasteners:

1/2" thick Gypsum Wall Board - No. 13 gauge, 1-3/8" long, 19/64" head; 0.098" diameter, 1-1/4" long, annular ringed; 5d, cooler or wallboard nail (0.086" dia., 1-5/8" long, 15/64" head).
Nails per ASTM C514

5/8" thick Gypsum Wall Board - No. 13 gauge, 1-5/8" long, 19/64" head; 0.098" diameter, 1-3/8" long, annular ringed; 6d, cooler or wallboard nail (0.0926" dia., 1-7/8" long, 1/4" head).
Nails per ASTM C514
Screws must be installed per ASTM C1002

SINGLE NAILING APPLICATION Figure 2 ASTM C840



DOUBLE NAILING APPLICATION

Figure 3 ASTM C840

Screws shall not be less than number 6 with major diameter not less than 0.136 inch. Type W and Type A screws shall be long enough to penetrate wood members not less than 5/8 inch. Ref. ASTM C1002